



AERMLED2/60/CW

Endurance LED Recessed Panel - 600 x 600 Cool White 30W



Features

High performance maintenance free LED Panel

Tpa as standard

30W Panel outperforms 3x14W T5

Low glare and even light distribution for multiple applications

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Panel Pod Self-Test emergency option

Panel Pod sensor option

Surface mounting frame option

Supplied c/w Philips LED driver

LED Lifespan L70 60,000 hours

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface/Recessed/Suspended
Diffuser Rating	Tp(a)
LED Life	L70 60,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Depth (mm)	10
Accessories	AIRMLD/SMF, AIRMLD/PRK, AERMLD/SK, AEQTCC/600

Technical Information

Wattage	30W
Lumens Delivered	3092lm
Lm/W	107lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 40°C



Technical Data - ETIM - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	No
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Protection class	II
Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Max. system power	30 W
Rated luminous flux acc. IEC 62722-2-1	3092 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Luminaire efficacy	107 lm/W
Width	595 mm
Height/depth	10 mm
Length	595 mm

Datasheet generated from <https://www.electrika.com> last updated Monday, November 4, 2019 2:43:04 PM