



AGLED/3M

Guardian LED Bulkhead Maintained / Non-Maintained 3W White



Features

Ultra-slim profile LED polycarbonate bulkhead.

Supplied with self-adhesive legend.

20mm side, end and rear cable entries.

Hinged screwless gear tray for ease of installation.

Viewing distance 18 metres.

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP65
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Width (mm)	352
Height (mm)	110
Depth (mm)	64
Accessories	AGLED/KIT, ASBP/2

Technical Information

Wattage	3W
Lumens Delivered	144lm (Emergency), 180lm (Standard)
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0C° to 40C°

Technical Data - ETIM - Emergency luminaire (EC001957)

Mounting method Wall surface mounted / ceiling surface mounting

Function Escape route lighting

Labelling type Sticker

With light source Yes

Material housing Plastic

Colour housing White

Nominal voltage 230-230 V

Degree of protection (IP) IP65

Protection class I

Max. system power 3 W

Rated luminous flux acc. IEC 62722-2-1 180 lm

Colour temperature 6500-6500 K

Recognition distance 18 m

Width 110 mm

Height/depth 64 mm

Length 352 mm

Datasheet generated from <https://www.electrika.com> last updated Monday, November 4, 2019 1:58:03 PM

