


415040

Technical Specification

truSmart Up/Down Linear 5ft 40W 4000k White



Product Information

Product Group	truSmart
Description	truSmart Up/Down Linear 5ft 40W 4000k White
Product Name	Smart Linear
Product Colour	White
Warranty	5 Years

General Information

IP Rating	IP20
Operating Temperature	-20°C - +40°C
Body Material	Aluminium
Diffuser Material	Polycarbonate
Mounting Type	Suspended
Control Type	Bluetooth





415040

Technical Specification

App Available

Yes

LED Information

LED Type	2835SMD
Lumen Output +/- 10%	Up: 880lm Down: 3120lm
LED Lifetime L70	50,000 Hours
сст	4000K
CRI	>80

Electrical Information

Circuit Wattage	40W
Class	Class I
Connection Type	Flying Lead

Driver Information

Driver Brand	Lumineux
Dimming	Wireless Dimming
Input Voltage	100 - 240V AC
Operating Frequency	50 - 60Hz
Power Factor	>0.95
Flicker Free	Yes

Sensor Information

Sensor Type

PIR





415040

Technical Specification

Mounting Height MAX	3M
Hold Time	1 Min - Infinite
Stand-by Level	0 - 100%
Stand-by Delay	0 Min - Infinite
Detection Area	6M
Daylight Sensor	App Controlled
Wireless Grouping	Yes

Shipping Information

Barcode

5055379535542

Certification

Manufactured in Accordance to	BS EN 60598-1	
CE Marked	Yes	





415040	Technical Specification

Datasheet generated by https://www.onetimepim.com, last updated: Thursday, 09 January 2020 14:28:34

Tel: 01507 328031 | Email: sales@lumineux.co.uk | www.lumineux.co.uk B&T Associates Ltd, Manby Business Park, Manby, Louth, Lincolnshire, LN11 8UT, UK Information and specification is subject to change without prior notice. Lumineux terms and conditions apply.

