



Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Socket-outlet
Device presentation	Complete product
Outlet standard description	Round pin
Switch function	Unswitch
Colour tint	Matt white
Quantity per set	Set of 1

Complementary

Outlet poles configuration	1P
Outlet standard	British
Number of gangs	1 gang
Device mounting	Wall mounted
Rated current	5 A at 230 V AC 50 Hz
Fixing mode	By screws M3.5 x 25 mm
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of packing	Box
Type of installation	Indoor
Height	87 mm
Width	87 mm
Depth	27.46 mm
Net weight	0.075 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	BS 546
IP degree of protection	IP20

Packing Units

Package 1 Weight	72.000 g
Package 1 Height	27.000 mm
Package 1 width	87.000 mm
Package 1 Length	87.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------