# Product datasheet Characteristics

# **GGBL5011**

Lisse - Fuse connection unit - LED - 1 gang - 13 A - white moulded





#### Main

Range	Lisse	
Aesthetic name	White moulded	
Product or component type	Fuse connection unit	
Device presentation	Complete product	
Colour tint	white moulded	
Quantity per set	Set of 10	

### Complementary

		(
Pilot light	LED	
Actuator	Rocker	
Number of gangs	1 gang	
Material	Urea (carbamide)	
Device mounting	Wall mounted	
Fixing mode	By screws	
Rated current	13 A at 250 V AC	<u>.</u>
Connections - terminals	Screw terminals	با
Type of packing	Carton	
Width	87 mm	<u> </u>
Height	87 mm	- \(\) \(\) \(\) \(\)
Depth	28 mm	
Net weight	0.105 kg	. <u></u>

#### Environment

Standards	BS 1363
IP degree of protection	IP20

# Packing Units

Package 1 Weight	105.000 g	
Package 1 Height	28.000 mm	
Package 1 width	87.000 mm	
Package 1 Length	87.000 mm	

# Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	-
Circularity Profile	End of Life Information	-

# Contractual warranty

Warranty	18 months
vvairanty	TO MONUIS