



Ultra Slim

LED Integrated Batten

- The smart replacement for Fluorescent Fixtures
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Cool white
- Quick and easy installation
- Shatterproof
- 3 year guarantee (Excluding Battery)³



Code	W	Description	Temp	lm	Hrs
10270	38	Ultra Slim LED Integrated - 4000K, Single 1230mm (4ft)	4000	4400	35000
10271	45	Ultra Slim LED Integrated - 4000K, Single 1530mm (5ft)	4000	5300	35000
10272	56	Ultra Slim LED Integrated - 4000K, Single 1850mm (6ft)	4000	6600	35000




¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio
² Exceeds EU standard of RA 80 for Colour Rendering Index
³ Subject to terms & conditions (Contact Customer Service)



Ultralim

Technical Specification

Data	
Construction	Aluminium Body, Polycarbonate lens
Driver	BELL
LED Chip	Samsung
IP Rating	IP20
Operating Temp	-30°C to +35°C / Emergency Version -10°C to +35°C
Input Voltage	220 - 240V
Power Factor	> 0.9
CRI	85 - Exceeds EU standard of Ra 80 for Colour Rendering Index
LMR	80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio
ECA Compliant	Yes
L1A / L1B / L2A / L2B Compliant	Yes



Model	A	B	D
38W	75mm	1230mm	26mm
45W	75mm	1530mm	26mm
56W	75mm	1850mm	26mm

