INCEPTOR® EVO


Technical Specification

Product Code: OV9500WH93EMST

Description: 12W LED Utility Bulkhead With Emergency Self Test - IP65 - 4200K - White








General Information

deficial information	
Dimensions	308mm Diameter x 93mm (D)
Materials	Base, Outer Ring, Circular Facia & Diffuser:
	Polycarbonate (UV Stabilised)
	Gear Tray, Driver Housing & Cable Grip:
	Polycarbonate (UV Stabilised)
	LED Array: Aluminium Substrate
	Moisture Seal: Silicone
Finish	White (RAL 9010)
Product Weight	1.48Kg
Cutout	282-286mm Diameter
	IP65
	Tp(a)
IK Rating	IK08
Mounting	Ceiling or Wall and Surface or Semi-recessed
Warranty	5 Years (4 Years Battery)

Accessories

OV9001BK/WH	Circular Metal Housing For Inceptor® EVO - Black or White
OV9002BK/WH	Eyelid Metal Housing For Inceptor® EVO - Black or White
OV9003BK/WH	Grille Metal Housing For Incentor® EVO - Black or White



Supply & Power

Input Voltage & Frequency	230V~ 50/60Hz
Electrical Safety	Class II (Double Insulated)
LED Wattage	10W
Circuit Wattage	12W
Input Current	107mA
Ambient Temperature (Ta)	-5°C - +45°C
LED Driver	Integrated
Prewired Flow [™] Connector	Yes (4 Pole CT203-F Screw Terminals)

Lummaire Output	
Colour Temperature	4200K
CRI	68.4
Typical Luminous Flux	1210lm
Efficacy	101lm/W
Beam Angle	120°
LED Lifetime (L70)	50,000 Hours

Emergency Information

gogg		
Self Test	Yes	
Installation Requirements	Can be wired as maintained or non-maintained	
Battery Specification	Ni-Cd 3000mAh 3.6V (Max Cell Temperature 50°C)	
Battery Warranty	4 Years	
Emergency Duration	3 Hours Minimum	













T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com

