

# **Technical Specification**



**Description:** 

Standalone IP55 External Battery Powered Surveillance Camera, Integrated recording via Built-in SD Card with vandal resistant housing





#### Camera

Outputs

	ø75mm x 140mm		Output AV Composite Video/Audio
Lens	High precision multi layer coated	USB (	Dutput Mini 5P -B Type USB
Focal Length	6mm (approx. 50° field of view)	Recorder	
Camera Angle	50°		SD Card, Maximum 32GB
Minimum Focal Capability	1.5m		*
White Balance	Automatic	Video Resolution	1
Exposure Control	Automatic	Still Image Resolution	3, 5 or 8MP
	10 ~ 12m Max.	Audio Recording	Yes; with video
PIR Angle		Still Image	$1 \sim 9$ ; burst selectable
PIR Colour	Black	Video Recording Length	$5 \sim 300$ Seconds
IR Distance	15 Metres	Stamping	Time & Date
Туре	Black Covert	Control	VIA Board Datascreen
Power		Recording Format	AVI
Operating Voltage	6VDC	Environment	

Ingress Protection IP55

### Power

Operating V

6VDC Power Adapter or 4 x C Type Power Source Batterys

## Construction

Material ABS Fixing Surface Only

### **Component Supplied**

User Manual 4 x C Type Batteries USB & AV composite Cable Steel Vandal Resistant Casing

## Features

1080p HD video resolution 8MP still image resolution Recording triggered via PIR or time lapse programming Internal SD card recording (4GB SD card Supplied: Up to 1000 still images or 100 video clips with full card overwrite) Battery or 6vdc powered Black covert infra-red illumination up to 15 meters for discreet low light level recording Simple transfer of recordings High quality fixed 6mm lens Camera Weatherproof Rating IP55



Page 1 of 1 Rev.1 Errors & Omissions excluded Specification is subject to change without notice